Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

TRUE/FALSE

1. Programming style includes techniques for consistently putting spaces and indentation in a program to help create visual cues.

   ANS: T

2. Both character and string literals can be assigned to a **`char`** variable.

   ANS: F

3. A variable's scope is the part of the program that has access to that variable.

   ANS: T

4. Named constants are initialized with a value and that value cannot change during the execution of the program.

   ANS: T

5. When you call one of the **`Scanner`** class's methods to read a primitive value, such as **`nextInt`** or **`nextDouble`**, and then call the **`nextLine`** method to read a string, an annoying and hard-to-find problem can occur.

   ANS: T

6. Class names and key words are examples of variables.

   ANS: F

7. The Java API provides a class named **`Math`** that contains numerous methods which are useful for performing complex mathematical operations.

   ANS: T

8. The **`System.out.printf`** method allows you to format output in a variety of ways.

   ANS: T

9. A Java program will not compile unless it contains the correct line numbers.

   ANS: F

10. Java is not case sensitive.

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

ANS: F

11. If the compiler encounters a statement that uses a variable before the variable is declared, an error will result.

ANS: T

MULTIPLE CHOICE

1. Which of the following is a value that is written into the code of a program?

a. a literal
b. an assignment statement
c. an operator
d. a variable

ANS: A

2. A Java program must have at least one of the following:

a. a comment
b. a class definition
c. a **`System.out.println();`** statement
d. a variable declaration

ANS: B

3. Which of the following would contain the translated Java byte code for a program named `Demo`?

a. `Demo.java`
b. `Demo.code`
c. `Demo.class`
d. `Demo.byte`

ANS: C

4. Which of the following is a named storage location in the computer's memory?

a. a literal
b. an operator
c. a constant
d. a variable

ANS: D

5. Which of the following is not a valid Java comment?

a. **`/** Comment one */`**
b. **`*/ Comment two /*`**
c. **`// Comment three`**
d. **`/* Comment four */`**

ANS: B

6. To compile a program named `First` you would use which of the following commands?

a. `java First.java`
b. `javac First`
c. `javac First.java`
d. `compile First.javac`

ANS: C

7. A Java source file must be saved with the extension

a. **`.java`**
b. **`.javac`**
c. **`.src`**
d. **`.class`**

ANS: A

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

8. Which of the following is not a rule that must be followed when naming identifiers?

   a. After the first character, you may use the letters a-z, A-Z, an underscore, a dollar sign, or the digits 0-9.
   b. Identifiers can contain spaces.
   c. Uppercase and lowercase characters are distinct.
   d. The first character must be one of the letters a-z, A-Z, an underscore, or a dollar sign.

   ANS: B

9. Character literals are enclosed in _____ and string literals are enclosed in _____.

   a. single quotes, double quotes
   b. double quotes, single quotes
   c. single quotes, single quotes
   d. double quotes, double quotes

   ANS: A

10. Variables are classified according to their

    a. names
    b. values
    c. locations
    d. data types

    ANS: D

11. What is the result of the following expression?

```
17 % 3 * 2 - 12 + 15
```

    a. `105` b. `12` c. `7` d. `8`

    ANS: C

12. What is the result of the following expression?

```
10 + 5 * 3 - 20
```

    a. `-5` b. `-50` c. `5` d. `25`

    ANS: C

13. In the following Java statement, what value is stored in the variable **`name`**?

```
String name = "John Doe";
```

    a. `"name"`
    b. the memory address where `"John Doe"` is located
    c. the memory address where `name` is located
    d. `John Doe`

    ANS: B

14. What is the value of **`z`** after the following statements have been executed?

```
int x = 4, y = 33;
double z;
z = (double) (y / x);
```

    a. `8.25` b. `4` c. `0` d. `8.0`

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

ANS: D

15. What output will be displayed as a result of executing the following code?

```
int x = 5, y = 20;
x += 32;
y /= 4;
System.out.println("x = " + x + ", y = " + y);
```

a. `x = 160, y = 80`
b. `x = 32, y = 4`
c. `x = 37, y = 5`
d. `x = 9, y = 52`

ANS: C

16. Which of the following statements will correctly convert the data type, if **x** is a **float** and **y** is a **double**?

a. `x = float y;`
b. `x = <float>y;`
c. `x = (float)y;`
d. `x = y;`

ANS: C

17. Which of the following statements is invalid?

a. `double r = 9.4632E15;`
b. `double r = 9.4632e15;`
c. `double r = 2.9X106;`
d. `double r = 326.75;`

ANS: C

18. To print **"Hello, world"** on the monitor, which of the following Java statements should be used?

a. `System.out.println("Hello, world");`
b. `System Print = "Hello, world";`
c. `SystemOutPrintln('Hello, world');`
d. `system.out.println(Hello, world);`

ANS: A

19. The **boolean** data type may contain which of the following range of values?

a. `-128 to + 127`
b. `true or false`
c. `-2,147,483,648 to +2,147,483,647`
d. `-32,768 to +32,767`

ANS: B

20. Variables of the **boolean** data type are useful for

a. evaluating conditions that are either true or false
b. working with small integers
c. working with very large integers
d. evaluating scientific notation

ANS: A

21. What would be displayed as a result of executing the following code?

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

```
int x = 578;
System.out.print("There are " +
x + 5 + "\n" +
"hens in the hen house.");
```

a. `There are 583`
   `hens in the hen house.`
b. `There are 5785`
   `hens in the hen house.`
c. `There are x5\nhens in the hen house.`
d. `There are 5785 hens in the hen house.`

ANS: B

22. What would be displayed as a result of executing the following code?

```
final int x = 22, y = 4;
y += x;
System.out.println("x = " + x + ", y = " + y)
```

a. `x = 22, y = 26`
b. `x = 22, y = 4`
c. `x = 22, y = 88`
d. Nothing. There is an error in the code.

ANS: D

23. What would be displayed as a result of executing the following code?

```
int x = 15, y = 20, z = 32;
x += 12;
y /= 6;
z -= 14;
System.out.println("x = " + x +
                   ", y = " + y +
                   ", z = " + z);
```

a. `x = 27, y = 3.333, z = 18`
b. `x = 27, y = 2, z = 18`
c. `x = 37, y = -14, z = 4`
d. `x = 27, y = 3, z = 18`

ANS: D

24. What is the value of **z** after the following code is executed?

```
int x = 5, y = 28;
float z;
z = (float) (y / x);
```

a. `5.6` b. `3.0` c. `5.0` d. `5.60`

ANS: C

25. Which of the following statements correctly creates a **Scanner** object for keyboard input?

a. `Scanner kbd = new Scanner(System.keyboard);`
b. `Scanner keyboard = new Scanner(System.in);`
c. `Scanner keyboard(System.in);`
d. `Keyboard scanner = new Keyboard(System.in);`

ANS: B

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

26. Which **`Scanner`** class method reads a **`String`**?

a. **`nextLine`**
b. **`charAt`**
c. **`nextString`**
d. **`getLine`**

ANS: A

27. The primitive data types only allow a(n) _____ to hold a single value.

a. class
b. literal
c. object
d. variable

ANS: D

28. In Java, _____ must be declared before they can be used.

a. variables
b. literals
c. key words
d. comments

ANS: A

29. If the following Java statements are executed, what will be displayed?

```
System.out.println("The top three winners are\n");
System.out.print("Jody, the Giant\n");
System.out.print("Buffy, the Barbarian");
System.out.println("Adelle, the Alligator");
```

a. The top three winners are
Jody, the Giant
Buffy, the Barbarian
Adelle, the Alligator

b. The top three winners are Jody, the Giant\nBuffy, the BarbarianAdelle, and the Albino

c. The top three winners are
Jody, the Giant\nBuffy, the BarbarianAdelle, the Alligator

d. The top three winners are
Jody, the Giant
Buffy, the BarbarianAdelle, the Alligator

ANS: D

30. A value that is written into the code of a program is a(n) _____.

a. literal
b. assignment statement
c. variable
d. operator

ANS: A

31. When the + operator is used with strings, it is known as the

a. assignment operator
b. string concatenation operator
c. addition operator
d. combines assignment operator

ANS: B

32. What would be printed out as a result of the following code?

```
System.out.println("The quick brown fox" +
```

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

```
                                "jumped over the \n"
                                "slow moving hen.");
```

a. The quick brown fox jumped over the \nslow moving hen.
b. The quick brown fox jumped over the
   slow moving hen.
c. The quick brown fox
   jumped over the
   slow moving hen.
d. Nothing - this is an error

ANS: D

33. Which of the following is ***not*** a rule that must be followed when naming identifiers?
a. The first character must be one of the letters a-z, A-Z, and underscore or a dollar sign.
b. Identifiers can contain spaces.
c. Uppercase and lowercase characters are distinct.
d. After the first character, you may use the letters a-z, A-Z, the underscore, a dollar sign, or digits 0-9.

ANS: B

34. Which of the following cannot be used as identifiers in Java?
a. variable names
b. class names
c. key words
d. objects

ANS: C

35. Which of the following is not a primitive data type?
a. `short`
b. `long`
c. `float`
d. `string`

ANS: D

36. Which of the following is valid?
a.
```
float y;
y = 54.9;
```
b.
```
float y;
double z;
z = 934.21;
y = z;
```
c.
```
float w;
w = 1.0f;
```
d.
```
float v;
v = 1.0
```

ANS: C

37. If `x` has been declared an `int`, which of the following statements is invalid?
a. `x = 0;`
b. `x = -59832;`
c. `x = 1,000;`
d. `x = 592`

ANS: C

38. To display the output on the next line, you can use the `println` method or use the _____ escape sequence in the `print` method.
a. `\n`
b. `\r`
c. `\t`
d. `\b`

ANS: A

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis

39. Every Java application program must have

a. a class named `MAIN`
b. a method named `main`
c. at least two data types
d. integer variables

ANS: B

40. What will be displayed as a result of executing the following code?

```
int x = 6;
String msg = "I am enjoying this class.";
String msg1 = msg.toUpperCase();
String msg2 = msg.toLowerCase();
char ltr = msg.charAt(x);
int strSize = msg.length();
System.out.println(msg);
System.out.println(msg1);
System.out.println(msg2);
System.out.println("Character at index x = " + ltr);
System.out.println("msg has " + strSize + "characters.");
```

a. I am enjoying this class.
I AM ENJOYING THIS CLASS.
i am enjoying this class.
Character at index x = e
msg has 24 characters.

b. I am enjoying this class.
I AM ENJOYING THIS CLASS.
i am enjoying this class.
Character at index x = e
msg has 25 characters.

c. I am enjoying this class.
I AM ENJOYING THIS CLASS.
i am enjoying this class.
Character at index x = n
msg has 24 characters.

d. I am enjoying this class.
I AM ENJOYING THIS CLASS.
i am enjoying this class.
Character at index x = n
msg has 25characters.

ANS: D

41. What will be displayed as a result of executing the following code?

```
public class test
{
   public static void main(String[] args)
   {
      int value1 = 9;
      System.out.println(value1);
      int value2 = 45;
      System.out.println(value2);
      System.out.println(value3);
      value = 16;
   }
}
```

a. 9
45
16

b. 94516

c. 9 45 16

d. Nothing. This is an error

ANS: D

Access Complete Test Bank for Starting Out with Java From Control Structures through Data Structures 4th Gaddis